

# Feed Cover



Your Trusted Source for Satellite Equipment



- Reduces exposure of Feed and RF Components to the elements
- For use with Quad or Tri Feed Supports
- Includes Mounting Hardware

Rectangular Feed Support Mounting	Round Feed Support Mounting
A photograph showing a rectangular metal plate with two pre-drilled holes. Two self-tapping screws are being used to secure the plate to a metal support structure.	A photograph showing a white cylindrical feed cover being held in place by two U-bolts attached to a metal bracket.
Drill into support with self-tapping screws	Use provided U-bolts to clamp to bracket

## Additional Information:

- Pre-drilled for 4 feed support configuration (90° holes)
- In the field adaptable to 3 feed support configuration (120° holes)
- Operator to bend brackets to match angle of feed supports
- Length = 27" / Diameter = 14.5" / Weight approximately 9 Lbs
- Ku band H-Bend needed if using FEED-4CKU\* and FEED-2KU-MOTO Series of Feeds

COV-FEED-VKG\_REV002  
Specifications are subject to change without notice

[sales@vikingsatcom.com](mailto:sales@vikingsatcom.com) • [www.vikingsatcom.com](http://www.vikingsatcom.com)

T: 517.629.3000 • F: 517.629.2379 • 704 North Clark Street • Albion, MI