

C/Ku Band, 4 Port Feeds



Your Trusted Source for Satellite Equipment



- **Receive Only 4 Port C/Ku band Prime Focus Feed**
- **Simultaneous Reception of Dual C & Dual Ku-Band Polarities**
- **Standard, Extended and High Band Options**

SPECIFICATIONS	C Band	Ku Band
Frequency:		
FEED-4CKU-ADL	3.7 – 4.2 GHz	10.70 – 12.75 GHz
FEED-4CKU-EXT	3.4 - 4.2 GHz	10.70 – 12.75 GHz
FEED-4CKU-ADL-H	3.7 - 4.8 GHz	10.70 - 12.75 GHz
FEED-4CCKU-ADL	3.6 - 4.2 GHz	10.70 – 12.75 GHz
VSWR (Typical)		
FEED-4CKU-ADL	1.5:1	1.6:1
FEED-4CKU-EXT	1.7:1	1.6:1
FEED-4CKU-ADL-H	3:1	1.6:1
FEED-4CCKU-ADL	1.7:1	1.6:1
Cross Pol Isolation (Linear / Circular)	LP 3.4-3.7=15dB / 3.7-4.2=18dB CP 15 dB	LP 25 dB
Number of Ports	2	2
Type of Ports	WR229	WR75
Polarization:		
FEED-4CKU-ADL, FEED-4CKU-EXT, FEED-4CKU-ADL-H	Linear	Linear
FEED-4CCKU-ADL	Circular	Linear
Weight	3.0 Lbs approx	

FEATURES:

- Simultaneous Reception of Dual C & Dual Ku-Band Polarities
- Universal Mounting - Mounts to single pole, tripod and quadpod feed supports
- For use with new antennas or upgrading existing antennas in the field
- Precision cast aluminum construction
- All Components Weather Resistant
- Stainless Steel Hardware
- Microwave transparent throat cover
- Durable flake resistant coating
- Made in the USA

FEED-4CKU_REV011

Specifications are subject to change without notice

sales@vikingsatcom.com • www.vikingsatcom.com

T: 517.629.3000 • F: 517.629.2379 • 704 North Clark Street • Albion, MI